

Compare Products

Code	71381
Model	Xjt



Note	<p>ERON D-1 DASHBOARD Connect Calypso Connect (Motor) Dual Speed trigger Fiber Carbon Proplock Propeller Battery Gauge Bypass System HD Shaft Seal Carry Handle Cleaning and Lubrication Kit Tow Leash with boltsnap and bungee Extra Bolt snap</p> <p>- Top speed is delivered with fully charged battery - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim - Conditions : sea water - no flow/current</p>
-------------	---

Dimensions

Use	TECH / COMMERCIAL
Length	mm 814 (inch 31,1)
Width	mm 436 (inch 17,2)
Height	mm 340 (inch 13,4)
Body diameter	mm 197 (inch 7,8)
Weight without battery	kg 14 (lb 30,9)
Weight with battery	kg 20 (lb 44,1)
Material type	Aluminum Body

Performance

Max static thrust	N 330 (lb 74,2)
Top speed	mt/min 85 (ft/min 278)
Run time at max speed/drag	min 35
Run time at cruise speed	min 95
Maximum operational depth	mt 200 (ft 656)
Test depth	mt 300 (ft 984)
Buoyancy/ trim	Neutral Trim and Buoyancy

In-water usage temperature °C -5/+35 (°F +23/+95)

Runtime-range

SPEED	BURNTIME	RANGE
FULL TRIGGER	35 MIN	2,4 (1,1) KM (nm)
60 MT/MIN	50 MIN	2,9 (1,5) KM (nm)
CRUISE 45 MT/MIN	75 MIN	3,2 (1,7) KM (nm)
30 MT/MIN	110 MIN	

- Top speed is delivered with fully charged battery
 - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim
 - Conditions : sea water - no flow/current

Battery type

Battery type	Nimh
Nominal Voltage	Volt 26,4
Nominal Capacity	Wh 370
Maximum recharging time	h 4,5
Charger power supply	90/240 - 50/60 Hz

Features

Smartphone connect	●
External Charge	
Battery Gauge	●
Li-ion Battery	
Fastening device	●
Main Switch	●
Proplock Propeller	●
Speed Adjustment	●
By-pass System	●
Easy Trim	●
Easy Inspect	●
New Handle Design	
Sealed Motor Compartment	●
NBS - Neutral Buoyancy System	●
Made Salt Resistant	●
Motor Protection	●
Battery Protection	●
Certifications	●

Features legend:

● : standard

O : optional

: not available