

## Compare Products

<b>Code</b>	<b>71382</b>
<b>Model</b>	<b>XK</b>



**Note**

**ERON D-1 DASHBOARD Connect**  
**Calypso Connect (Motor, Battery, ERON D-1)**  
**Dual Speed trigger**  
**Fiber Carbon Proplock Propeller**  
**Battery Gauge**  
**Bypass System**  
**HD Shaft Seal**  
**Carry Handle**  
**Cleaning and Lubrication Kit**  
**Tow Leash with boltsnap and bungee**  
**Extra Bolt snap**

- Top speed is delivered with fully charged battery  
 - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim  
 - Conditions : sea water - no flow/current

## Dimensions

<b>Use</b>	TECH / COMMERCIALLONG RANGE / CAVE
<b>Length</b>	mm 975 (inch 38,4)
<b>Width</b>	mm 462 (inch 18,2)
<b>Height</b>	mm 364 (inch 14,33)
<b>Body diameter</b>	mm 197 (inch 7,8)
<b>Weight without battery</b>	kg 17 (lb 37,48)
<b>Weight with battery</b>	kg 25 (lb 55,12)
<b>Material type</b>	Aluminum Body

## Performance

<b>Max static thrust</b>	N 375 (lb 84,3)
<b>Top speed</b>	mt/min 100 (ft/min 328)
<b>Run time at max speed/drag</b>	min 100
<b>Run time at cruise speed</b>	min 330
<b>Maximum operational depth</b>	mt 200 (ft 656)
<b>Test depth</b>	mt 300 (ft 984)
<b>Buoyancy/ trim</b>	Neutral Trim and Buoyancy

**In-water usage temperature**

°C -5/+35 (°F +23/+95)

**Runtime-range**

SPEED	BURNTIME	RANGE
FULL TRIGGER	100 MIN	8,1 (4,4) KM (nm)
80 MT/MIN	120 MIN	9,6 (5,2) KM (nm)
60 MT/MIN	200 MIN	12,0(6,5) KM (nm)
CRUISE 45 MT/MIN	330 MIN	14,8(8,0) KM (nm)

- Top speed is delivered with fully charged battery  
- Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim  
- Conditions : sea water - no flow/current

### Battery type

<b>Battery type</b>	LI-ion
<b>Nominal Voltage</b>	Volt 36
<b>Nominal Capacity</b>	Wh 1340
<b>Maximum recharging time</b>	h 8
<b>Charger power supply</b>	90/240 - 50/60 Hz

### Features

<b>Smartphone connect</b>	●
<b>External Charge</b>	
<b>Battery Gauge</b>	●
<b>Li-ion Battery</b>	●
<b>Fastening device</b>	●
<b>Main Switch</b>	●
<b>Proplock Propeller</b>	●
<b>Speed Adjustment</b>	●
<b>By-pass System</b>	●
<b>Easy Trim</b>	●
<b>Easy Inspect</b>	●
<b>New Handle Design</b>	●
<b>Sealed Motor Compartment</b>	●
<b>NBS - Neutral Buoyancy System</b>	●
<b>Made Salt Resistant</b>	●
<b>Motor Protection</b>	●
<b>Battery Protection</b>	●
<b>Certifications</b>	●

**Features legend:**

● : standard

○ : optional

  : not available